

WHAT IS CLAIMED IS:

- Sub
H1
- 10093467-020702
1. An image heating apparatus for heating an image formed on a recording material, comprising:
a heater, said heater including a metallic
5 substrate;
a film moving in contact with said heater; and
a back-up roller for defining a nip with said heater via said film;
wherein said metallic substrate has a convex
10 surface on a side of the nip and a concave surface on an opposite surface.
 2. An image heating apparatus according to claim 1, wherein said metallic substrate is obtained
15 by bending a flat metal plate.
 3. An image heating apparatus according to claim 1, wherein said metallic substrate has an arch-
20 shape.
 4. An image heating apparatus according to claim 1, further comprising a holder for holding said heater, a surface on a side of the nip of said holder being connected smoothly to a surface on the side of
25 the nip of said heater.
 5. An image heating apparatus according to

claim 4, wherein a curvature of the surface on the nip side of said holder is substantially same as a curvature of the surface on the nip side of said heater.

5

6. An image heating apparatus according to claim 4, wherein said holder has a guide surface for guiding said film.

10

7. An image heating apparatus according to claim 1, wherein said heater has a first insulating layer on said metallic substrate, a heat generating resistor layer on said first insulating layer and a second insulating layer on said heat generating resistor layer.

15

8. An image heating apparatus according to claim 7, wherein said second insulating layer of said heater is in contact with said film.

20

9. An image heating apparatus according to claim 1, wherein a width in a moving direction of the recording material of said metallic substrate is greater than a width of the nip.

25

10. An image heating apparatus according to claim 9, wherein said metallic substrate has a

Sub
A1
cont

10091467-030702

cylindrical shape.

Sub
R1
cont

11. An image heating apparatus according to
claim 10, wherein said metallic substrate is fixed so
5 as not to rotate with respect to said apparatus.

12. An image heating apparatus according to
claim 1, wherein a thickness of said metallic
substrate is in a range of 0.5 mm to 2 mm.

10 13. An image heating apparatus according to
claim 1, wherein said film has an elastic layer.

14. A heater comprising:
15 a metallic substrate; and
a heat generating resistor;
wherein said metallic substrate has a convex
surface on one side and a concave surface on an
opposite side.

20 15. A heater according to claim 14, wherein
said heat generating resistor is provided on the
convex surface of said metallic substrate.

25 16. A heater according claim 14, further
comprising a first insulating layer on said metallic
substrate, wherein said heat generating resistor

10091457-030702

layer is provided on said first insulating layer and a second insulating layer is provided on said heat generating resistor layer.

5 17. A heater according to claim 14, wherein said metallic substrate has a cylindrical shape.

18. A heater according to claim 14, wherein a thickness of said metallic substrate is in a range of
10 0.5 mm to 2 mm.

Sub
M
Cust

10001457.030702